Fusion Edge 2000 Node

SD-WAN Node Specifications

Overview

The Fusion Edge 2000 Node is powered by the i3 8100, with 6 x 1Gbps Ethernet ports in a single RU rack mount format supporting up to 2Gbps of SD-WAN traffic.

Features

- 2 x DDR4 DIMM RAM slot, support 2133/2400/2666MHz, up to 64GB
- 6 x Intel WGI211AT Gigabit Ethernet, support Wake On LAN、PXE,4* Gigabit SFP port expansion
- 1 x CISCO RS232 COM
- 2 x USB3.0 port,1 x VGA display port
- 1U AC220V ATX power supply
- 1U rack amount case, galvanized steel



Model No.		Fusion Edge 2000 Node (1U 19" Rackmount)
Case	Material	1U rack mount case, high quality galvanized steel case
	Colour	Iron Gray
	Dimension (mm) (LxWxH)	430 x 320 x 44.5
	Installation	1U rack mount
Motherboard	CPU	I3 8100
	Chipset	Intel B250 Express chipset
	Graphics	Integrated Intel®HD Graphics
	Memory	2 x DDR4 DIMM RAM slot, 2133/2400/2666MHz, up to 64GB
Front Panel I/O	Power	1 x Power switch 1 x Reset switch
	USB	2 x USB2.0
	LAN	6 x Intel WGI211AT Gigabit Ether- net, support Wake On LAN、PXE function
	Dual SFP Ports	4 x Gigabit SFP port (expansion)
	СОМ	1 x CISCO RS232 COM port
	LED	1 x HDD, 1 x Power, 4 x SFP, 2 x data transfer

Rear Panel I/O	Display Port	1 x VGA port
	Power Port	1 x AC power port
Storage	SATA	2 x 2.5" SATA port
Expansion	Mini PCIE	1 x PCIE X8 slot, for 1G, 10GB SFP card expansion
OS Support	Microsoft Windows	Windows 7 (not include OS code)
	Linux	Ubunto
Power Type		AC 220V 1U ATX 250W
Environment	Working temp.	-10°∼60°
	Storage temp.	-20°~70°
	Relative Humidity	5%-95% relative humidity, non- condensing
	Working Vibration	0.5g rms/5-500HZ/random/ operating
Warranty		12 months or as long as the node is an active SD-WAN Node though Fusion Broadband

Contact Fusion Broadband

For more information about how the *Fusion Broadband Bandwidth Aggregation* can increase your speed, please call **+27 83 442 3396** or email our sales team at **info@fusionbroadband.co.za**.

